



GENERAL NOTES

Where at any time, any vehicle, equipment, workers or their activities will encroach in the area between the center line and a line 600 mm (24") outside the edge of pavement.

* Cones at 8 m (25') centers for 105 m (350'). Additional cones may be placed at 15 m (50') centers. When drums or barricades are used, the interval between devices may be doubled.

** Flaggers shall be positioned in advance of the work operation and remain there until the lane is open to traffic.

When the distance between successive patches is less than 450 m (1500'), the entire operation may be considered as one work area for flagging and signing purposes. When the distance between successive patches exceeds 450 m (1500'), additional warning signs, flaggers, and taper shall be used.

All dimensions are in millimeters (inches) unless otherwise shown.

SYMBOLS

- Work area
- Sign
- Barricade or drum
- Cone, drum or barricade
- Flagger with traffic control sign

TYPICAL APPLICATIONS

Patching
Utility operations
Storm sewer
Culvert
Cable placement

Illinois Department of Transportation	
APPROVED January 1, 2000 ENGINEER OF OPERATIONS APPROVED January 1, 2000 ENGINEER OF DESIGN AND ENVIRONMENT	ISSUED 1-1-97

DATE	REVISIONS
1-1-00	Rev. TYPICAL APPLICATION & detail of patch area.
1-1-97	Renum. Standard 2303-10.
	Deleted orange flags.
	Revised 2nd GN.

**LANE CLOSURE, 2L, 2W, DAY ONLY
ON-RD TO 600 mm (24") OFF-RD
FOR SPEEDS \geq 45 MPH**

STANDARD 701201-01